



## Panama Side Curtain

### TECHNICAL DATA SHEET

Product Code: CK007

Item	Unit	Test Method	Value			
Yarn	N/A	DIN 60001	100% Polyester			
Base Fabric	Denier	DIN EN ISO 2060	1000*1000			
Construction	/Inch	N/A	30*30 Panama weave			
Standard Weight	gsm	DIN EN ISO 2286-2	900			
	oz	ASTM D751	26.5			
Width	M	/	1.00~3.20			
	Inch	/	36~126			
Tensile Strength	N/5cm	DIN 53354	Warp	4000		
			Weft	3400		
Tearing Strength	N	DIN 53363	Warp	600		
			Weft	500		
Adhesion Strength	N/5cm	DIN 53357	100			
Flame Resistance	NFPA 701/ B1/ B2 (upon request)					
Temperature Resistance	-30°C-70°C					
Storage Condition	15°C-30°C 30%-60% Humidity					

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be for the purpose of lawsuit or warranty.

**Hangzhou Suntex Industries Co., Ltd**

15th Floor, Building No. 1, Guangrui Buinesee Center, Gongshu District,  
Hangzhou City, Zhejiang Province, China

Postal Code 310015

[www.suntexpro.com](http://www.suntexpro.com)

info@suntexpro.com