



Premium Coated PVC Blockout

TECHNICAL DATA SHEET

Product Code: SDC610

Item	Unit	Test Method	Value		
Yarn	N/A	DIN 60001	100% Polyester		
Base Fabric	Denier	DIN EN ISO 2060	500*500		
Construction	/Inch	N/A	28*28		
Standard Weight	gsm	DIN EN ISO 2286-2	610		
Width	M	N/A	Max up to 5.00		
Tensile Strength	N/5cm	DIN EN ISO 1421	Warp	1730	
			Weft	1330	
Tearing Strength	N	DIN 53363	Warp	311	
			Weft	266	
Flame Resistance	Can do NFPA 701/ B1/ B2/ M2 upon request				
Storage Condition	15°C-30°C 30%-60% Humidity				
Shelf Life	12 Months				
Inks Compatibility	Solvent / ECO-Solvent / UV / Latex				

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be for the purpose of lawsuit or warranty.

Hangzhou Suntex Industries Co., Ltd

15th Floor, Building No. 1, Guangrui Business Center, Gongshu District,
Hangzhou City, Zhejiang Province, China

Postal Code 310015

www.suntexpro.com

info@suntexpro.com